## 6000 SERIES



## Tough Efficient Effortless











## TRACTOR SPECIFICATIONS

TRACTOR	6060 2WD	6060 4WD	6065 2WD	6065 4WD	6075 2WD	6075 4WD
ENGINE						
Туре	Four Stroke, Direct Injection, Turbocharged, Water Cooled Diesel Engine					
Cylinders	4	4	4	4	4	4
Engine HP @ rpm	55 HP @ 1950	55 HP @ 1950	62 HP @ 1950	62 HP @ 1950	73 HP @ 1950	73 HP @ 1950
Displacement cubic (cc)	3533	3533	3855	3855	3822	3855
ELECTRICAL						
Battery Capacity	12 V, 100 AH					
Alternator	12 V, 90 A					
CLUTCH						
Туре	Dual Diaphragm Type					
TRANSMISSION						
Туре	Partial Synshromesh Opt: Synchro Shuttle	Partial Synshromesh with Synchro Shuttle	Partial Synshromesh Opt: Synchro Shuttle	Pertial Synshromesh with Synchro Shuttle	Partial Synshromesh Opt: Synchro Shuttle	Partial Synshromesh with Synchro Shuttle
Number of Gears/Speeds	15 Forward, 3 Reverse (Optional - 15 Forward, 15 R)	15 Forward, 15 Reverse	15 Forward, 3 Reverse (Optional - 15 Forward, 15 R)	15 Forward, 15 Reverse	15 Forward, 3 Reverse (Optional - 15 Forward, 15 R)	15 Forward, 15 Reverse
STEERING						
Туре	Hydrostatic Power Steering					
BRAKES						
Туре	Mechanical, Oil Immersed, Multi Disc Brakes					
HYDRAULIC SYSTEM						
Туре	Live Hydraulics with draft & position control	Live Hydraulics with draft & position control	Live Hydraulics with draft & position centrol	Live Hydraulics with draft & position control	Live Hydraulics with draft & position control	Live Hydraulics with draft & position control
3-Point Linkage	Cat I/II with stabilizer and fixed lower link	Cat I/II with stabilizer and fixed lower link	CAT I/II with Adjustable Stabilizer and telescopic lower link	CAT I/II with Adjustable Stabilizer and telescopic lower link	CAT I/II with Adjustable Stabilizer and telescopic lower link	CAT I/II with Adjustable Stabilizer and telescopic lower link
Lift Capacity (Kg.)	5500	2200	2600	2600	2600	2600
Rear Auxiliary Remote Valves	Double spool					
РТО						
Туре	SUPTO	SLIPTO	SLIPTO	SLIPTO	SLIPTO	SLIPTO
PTO RPM (engine rpm)	540 @ 1950/540E @ 1409	540 @ 1950/540E @ 1408				
PTO HP	48	48	54.5	54.5	64	64
OPERATING WEIGHT						
Total (Kg.)	3100	3310	3165	3375	3165	3375
DIMENSIONS with Ag Tires						
Overall Length Inches (mm)	4020	3660	4020	4020	4020	4020
Overall Width Inches (mm)	1960	1960	1990	1990	1990	1990
TIRES Sizes and Options						
Ag (Front /Rear)	7.5 X 16 16.9 X 28	9.5 x 24 16.9 X 28	7.5 X 16 16.9 X 30	11.2 x 24 16.9 X 30	7.5 X 16 16.9 X 30	11.2 X 24 16.9 X 30

Distributed in Namibia by







\*Mahindra & Mahindra is the No1 Tractor company in the world by volume



## Autohaus Windhoek (Pty) Ltd

For more information call +264 61 414 150 081 841 0741 - Ernest.Thatcher@metjeziegler.com 081 145 7106 - Adriaan.Lacock@metjeziegler.com 081 563 4591 - miltyfarming@gmail.com

