

7500 SERIES



# Tough Efficient Effortless



DEVING PRIZE



JAPAN QUALITY  
MEDAL

No. **1** Tractor  
Company  
in the World\*

**Mahindra**  
Tractors

\* Mahindra & Mahindra is the No1 Tractor Company in the World by volume

# TRACTOR SPECIFICATIONS

TRACTOR	7580 2WD	7580 4WD	7590 2WD	7590 4WD
<b>ENGINE</b>				
Type	Four Stroke, Direct Injection, Turbo-charged & Inter Cooled, Water-cooled, Diesel Engine	Four Stroke, Direct Injection, Turbo-charged & Inter Cooled, Water-cooled, Diesel Engine	Four Stroke, Direct Injection, Turbo-charged & Inter Cooled, Water-cooled, Diesel Engine	Four Stroke, Direct Injection, Turbo-charged & Inter Cooled, Water-cooled, Diesel Engine
Cylinders	4	4	4	4
Engine HP @ rpm	80 HP @ 2300	80 HP @ 2300	92 HP @ 2300	92 HP @ 2300
Displacement cubic (cc)	3533	3533	3533	3533
<b>ELECTRICAL</b>				
Battery Capacity	12 V, 88 Ah	12 V, 88 Ah	12 V, 80 Ah	12 V, 80 Ah
Alternator	12 V, 55 A	12 V, 55 A	12 V, 55 A	12 V, 55 A
<b>CLUTCH</b>				
Type	Dual Clutch	Dual Clutch	Dual Clutch	Dual Clutch
<b>TRANSMISSION</b>				
Type	Forward - Reverse Shuttle With Synchromesh Gear Shift	Forward - Reverse Shuttle With Synchromesh Gear Shift	Forward - Reverse Shuttle With Synchromesh Gear Shift	Forward - Reverse Shuttle With Synchromesh Gear Shift
Number of Gears / Speeds	12 Forward, 12 Reverse	12 Forward, 12 Reverse	12 Forward, 12 Reverse	12 Forward, 12 Reverse
<b>STEERING</b>				
Type	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering
<b>BRAKES</b>				
Type	Oil Immersed Brakes	Oil Immersed Brakes	Oil Immersed Brakes	Oil Immersed Brakes
<b>HYDRAULIC SYSTEM</b>				
Type	Open Center, Full-live Hydraulic With Position And Draft Controls	Open Center, Full-live Hydraulic With Position And Draft Controls	Open Center, Full Live Hydraulic With Position And Draft Controls	Open Center, Full Live Hydraulic With Position And Draft Controls
3-Point Linkage	Cat II Linkages With Stabilizer Bar	Cat II Linkages With Stabilizer Bar	Cat II Linkages With Stabilizer Bar	Cat II Linkages With Stabilizer Bar
Lift Capacity [Kg.]	2500	2500	2500	2500
Rear Auxiliary Remote Valves	Double	Double	Double	Double
<b>PTO</b>				
Type	Independent PTO	Independent PTO	Independent PTO	Independent PTO
PTO RPM (engine rpm)	540 @ 2186 & 1000 @ 2180	540 @ 2186 & 1000 @ 2180	540 @ 2186 & 1000 @ 2180	540 @ 2186 & 1000 @ 2180
PTO HP	65	65	74	74
<b>OPERATING WEIGHT</b>				
Total [Kg.]	3508	3698	3508	3698
<b>DIMENSIONS with Ag Tires</b>				
Overall Length (mm)	4115	4115	4115	4115
Overall Width (mm)	1963	1963	1963	1963
<b>TIRES Sizes and Options</b>				
Ag (Front / Rear)	7.5 X 16 / 10.0 X 16 (opt) 16.9 X 30 / 18.4 X 30 (opt)	11.2 X 24 / 12.4 X 24 (opt) 16.9 X 30 / 18.4 X 30 (opt)	10.0 X 16 18.4 X 30	12.4 X 24 18.4 X 30

Distributed in Namibia by

**No. 1 Tractor Company in the World\***



\*Mahindra & Mahindra is the No1 Tractor company in the world by volume

**Autohaus Windhoek (Pty) Ltd**

 **At home in Namibia**

For more information call +264 61 414 150  
081 841 0741 - Ernest.Thatcher@metjeziegler.com  
081 145 7106 - Adriaan.Lacock@metjeziegler.com  
081 563 4591 - miltyfarming@gmail.com

**Mahindra**  
Rise.